

Fujitsu Siemens ESPRIMO Edition P2530- Micro tower – DUAL CORE E2200 2GHz CPU+ - 1GB RAM - HD 1 x 250GB – DVD+-RW - Gigabit Ethernet – Vista & Win XP Pro Twin load - Monitor : none



The ESPRIMO P2530 is designed for price-conscious customers and is equipped with state-of-the-art standard Intel technology. These systems meet every office requirement - especially those typical for small and medium-sized businesses.

*\*We recommend if you are planning to use all the Vista Business Features that you upgrade the RAM to 2 GB ( 1 x Extra SDRAM) approx £45. This will insure you have plenty of resources and power for Office 2007*

**Add MS Office 2007 for Only extra £70 !**

Specification	Value
Type	Personal computer
Windows Vista Certification	Windows Vista Premium Ready
Product Form Factor	Micro tower
Width	20.2 cm
Depth	37.6 cm
Height	37.2 cm
Weight	11 kg
<b>Processor</b>	
Specification	Value
Type	Intel Pentium Dual Core E2200 / 2.2 GHz
Multi-Core Technology	Dual-Core
64-bit Computing	Yes
Installed Qty	1
Max Supported Qty	1
Upgradability	Upgradable
<b>Cache Memory</b>	
Specification	Value
Type	L2 Cache

Installed Size	1 MB
Cache Per Processor	1 MB
<b>Mainboard</b>	
<b>Specification</b>	<b>Value</b>
Chipset Type	NVIDIA GeForce 7050 / nForce 630i
Data Bus Speed	800 MHz
<b>RAM</b>	
<b>Specification</b>	<b>Value</b>
Installed Size	1 GB / 4 GB (max)
Technology	DDR2 SDRAM
Form Factor	DIMM 240-pin
Configuration Features	1 x 1 GB
<b>Storage Controller</b>	
<b>Specification</b>	<b>Value</b>
Type	1 x Serial ATA - integrated
Controller Interface Type	Serial ATA-300
Channel Qty	3
<b>Storage</b>	
<b>Specification</b>	<b>Value</b>
Hard Drive	1 x 250 GB - standard - Serial ATA-300 - 7200 rpm
<b>Optical Storage</b>	
<b>Specification</b>	<b>Value</b>
Type	DVD±RW (±R DL) / DVD-RAM - Serial ATA
<b>Monitor</b>	
<b>Specification</b>	<b>Value</b>
Monitor Type	None.
<b>Graphics Controller</b>	
<b>Specification</b>	<b>Value</b>
Type	Integrated
Graphics Processor / Vendor	NVIDIA GeForce 7050 Shared Video Memory (UMA)
Max Allocated RAM Size	256 MB
<b>Audio Output</b>	
<b>Specification</b>	<b>Value</b>
Type	Sound card - integrated
Compliant Standards	High Definition Audio

Input Device	
<b>Specification</b>	<b>Value</b>
Type	Mouse, keyboard
Mouse	
<b>Specification</b>	<b>Value</b>
Technology	Optical
Interface	USB
Features	Scroll
Networking	
<b>Specification</b>	<b>Value</b>
Networking	Network adapter - integrated
Data Link Protocol	Ethernet, Fast Ethernet, Gigabit Ethernet
Features	Wake on LAN (WoL), PXE support
Expansion / Connectivity	
<b>Specification</b>	<b>Value</b>
Expansion Bays Total (Free)	1 ( 0 ) x internal - 3.5" ; 1 ( 1 ) x front accessible - 3.5" ; 2 ( 1 ) x front accessible - 5.25"
Expansion Slots Total (Free)	1 ( 0 ) x processor - LGA775 Socket ; 2 ( 1 ) x memory - DIMM 240-pin ; 1 ( 1 ) x PCI Express x16 ; 2 ( 2 ) x PCI
Interfaces	1 x audio - line-in/microphone - mini-phone stereo 3.5 mm ; 1 x audio - line-In - mini-phone stereo 3.5 mm ; 1 x audio - line-out - mini-phone stereo 3.5 mm ; 1 x headphones - output - mini-phone stereo 3.5 mm ( 1 in front ) ; 1 x microphone - input - mini-phone 3.5mm ( 1 in front ) ; 8 x Hi-Speed USB - 4 PIN USB Type A ( 2 in front ) ; 1 x display / video - VGA - 15 pin HD D-Sub (HD-15) ; 1 x serial - RS-232 - 9 pin D-Sub (DB-9) ; 1 x network - Ethernet 10Base-T/100Base-TX/1000Base-T - RJ-45
Miscellaneous	
<b>Specification</b>	<b>Value</b>
Features	Security lock slot (cable lock sold separately), administrator password, system password
Compliant Standards	CE, GS, RoHS, WEEE
Power	
<b>Specification</b>	<b>Value</b>
Device Type	Power supply
Voltage Required	AC 230V ( 50/60 Hz )
Power Provided	300 Watt
Operating System / Software	
<b>Specification</b>	<b>Value</b>
OS Provided	Microsoft Windows Vista Business / XP Professional TwinLoad

Software	Drivers & Utilities, Microsoft Office Ready
<b>Manufacturer Warranty</b>	
<b>Specification</b>	<b>Value</b>
Service & Support	1 year warranty
Service & Support Details	Limited warranty - parts and labour - 1 year - on-site
<b>Environmental Parameters</b>	
<b>Specification</b>	<b>Value</b>
Min Operating Temperature	15 °C
Max Operating Temperature	35 °C